

Internationally approved



Fence-line Monitoring of Fugitive Emissions



Fence-line Monitoring of Fugitive Emissions

An Opsis air quality monitoring system gathers data along one or more light paths, each of which may be some hundreds of metres. This makes Opsis an ideal fence-line monitor, since a light path will act as a trip-wire to detect fugitive emissions.

An Opsis system will simultaneously monitor several user-defined compounds. More information is included on the reverse page, but typical examples are nitric oxide (NO), ammonia (NH₃), sulphur dioxide (SO₂), formaldehyde, benzene, toluene, phenol and other hydrocarbons. It is therefore possible to specify a system to monitor the emissions from for instance an industrial estate or a manufacturing complex.

Because Opsis will monitor the entire length of a boundary, and because it monitors several compounds simultaneously, it is more efficient and cost-effective than a number of point monitors for individual compounds. Continuously generated data is stored by the system's analyser. This allows information to be presented as averages for any user-defined interval – minutes, hours or days – either in real time or retrospectively.

The Opsis Technique

A basic Opsis system includes an analyser connected by a fibre optic cable to a light path created by a light emitter and a receiver. Several light paths may be run from a single analyser. The system may be permanently installed or operated from a mobile facility such as a specially equipped vehicle.

In either case the analyser will accept data from other devices producing a 4–20 mA or a digital output. This allows information from meteorological sensors (wind

strength and direction, temperature etc.) to be presented with air quality data to give a more detailed picture of environmental events. In the same way, Opsis will accept information from devices such as radiation monitors.

Tests and Approvals

Opsis has been tested and approved by a number of internationally recognized institutes and authorities. The system meets the requirements of U.S. EPA, MCERTS and TÜV. Full details are available on request.


Opsis – the Total Monitoring Solution


The Opsis long-path air quality monitoring system brings new standards of accuracy and data quality to environmental monitoring. Every minute, several thousand cubic metres of air interact with a beam of light between the light source, the emitter, and the receiver. When captured by the receiver, this light contains information on gases in the air it has penetrated.

This information is extracted by spectrographic analysis. Results are logged as data that can be collected for further analysis by modem – from anywhere in the world.

Opsis offers the total monitoring solution including software for data handling and management. In addition, Opsis offers dust monitors and conventional analysers.

Opsis technology is subject to a continual process of development. With the modular construction of Opsis systems, it is always possible to expand or update an installation without redundancy of viable equipment.





An Opsis system acting as a fence-line monitor detecting fugitive emissions

Performance Data (typical data which may vary depending on application)

Compound	Max. measurement range ⁽³⁾ (500 m path) ⁽⁴⁾	Min. detectable quantities (monitoring path 500 m, measurement time 1 min.)	Zero drift (500 m path, max. per month)	Span drift (per month, better than)	Span drift (per year, better than)	Linearity error (of measurement range, better than)	Max. length of fiber optic cable (when measuring several compounds) ⁽¹⁾	Hardware requirement
AR500/AR520 Analyser								
NO ₂	0-2000 µg/m ³	1 µg/m ³	±2 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
SO ₂	0-5000 µg/m ³	1 µg/m ³	±2 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
O ₃	0-1000 µg/m ³	2 µg/m ³	±4 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
NO ₂ ⁽²⁾	0-2000 µg/m ³	2 µg/m ³	±4 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
NH ₃ ⁽²⁾	0-500 µg/m ³	2 µg/m ³	±4 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
NO _x	0-500 µg/m ³	0.1 µg/m ³	±0.2 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
HNO ₂	0-2000 µg/m ³	1 µg/m ³	±2 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
HF	0-2000 µg/m ³	20 µg/m ³	±40 µg/m ³	±2%	±4%	±1%	10 m	AR520
Hg	0-2000 µg/m ³	20 ng/m ³	±40 ng/m ³	±2%	±4%	±1%	10 m	AR500/520
H ₂ O	0-100 g/m ³	0.2 g/m ³	±0.4 g/m ³	±2%	±4%	±1%	10 m	AR520
Styrene	0-2000 µg/m ³	5 µg/m ³	±10 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
CS ₂	0-2000 µg/m ³	20 µg/m ³	±40 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
Formaldehyde	0-2000 µg/m ³	2 µg/m ³	±4 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
Acetaldehyde	0-2000 µg/m ³	20 µg/m ³	±40 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
Phenol	0-2000 µg/m ³	1 µg/m ³	±2 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
Benzene	0-2000 µg/m ³	1 µg/m ³	±2 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
Toluene	0-2000 µg/m ³	1 µg/m ³	±2 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
p-, m-Xylene	0-2000 µg/m ³	1 µg/m ³	±2 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
o-Xylene	0-2000 µg/m ³	10 µg/m ³	±20 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
o-, m-, p-Cresol	0-2000 µg/m ³	5 µg/m ³	±10 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
C ₆ H ₅ Cl	0-2000 µg/m ³	5 µg/m ³	±10 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
C ₆ H ₄ Cl ₂	0-2000 µg/m ³	5 µg/m ³	±10 µg/m ³	±2%	±4%	±1%	10 m	AR500/520
LD500 Laser Diode Gas Analyser								
CO	0-100 mg/m ³	100 µg/m ³	±200 µg/m ³	±2%	±4%	±1%	500 m	LD500
CO ₂	0-100 g/m ³	1 mg/m ³	±2 mg/m ³	±2%	±4%	±1%	500 m	LD500
NH ₃	0-100 mg/m ³	20 µg/m ³	±40 µg/m ³	±2%	±4%	±1%	500 m	LD500
HCl	0-100 mg/m ³	20 µg/m ³	±40 µg/m ³	±2%	±4%	±1%	500 m	LD500
HF	0-10 mg/m ³	1 µg/m ³	±2 µg/m ³	±2%	±4%	±1%	500 m	LD500
CH ₄	0-100 mg/m ³	50 µg/m ³	±100 µg/m ³	±2%	±4%	±1%	500 m	LD500
H ₂ O	0-100% vol.	0.1% vol.	±0.2% vol.	±2%	±4%	±1%	500 m	LD500

⁽¹⁾ When monitoring individual compounds, fibre optic cables of extended lengths are available.

⁽²⁾ Based on 200 m path. Recommended monitoring path length: 100 to 200 m.

⁽³⁾ Higher measurement ranges are possible depending on application and compound.

⁽⁴⁾ Recommended monitoring path length: 300 to 800 m.

• Besides the compounds above, the Opsis system monitors the following compounds: hydrogen cyanide (HCN), hydrogen bromide (HBr), hydrogen chloride (HCl), chlorine dioxide (ClO₂), chlorine (Cl₂), carbon dioxide (CO₂), phosgene (COCl₂), ethylbenzene (C₆H₅C₂H₅), methane (CH₄), ethane (C₂H₆), ethylene (C₂H₄), acrylonitrile (CH₂=CHCN), 1,2,4-trimethylbenzene, 1,3,5-trimethylbenzene and others.

Please contact your Opsis supplier to discuss your particular system requirements, including the compounds you wish to monitor. Separate product sheets are available describing individual items of Opsis system hardware.
Specifications subject to change without notice.

Why Opsis?

Multi-gas and multi-path system

Combines the benefits of UV/FTIR DOAS and TDL technology

Total monitoring solution

Cost-effective, open-path technology

High-performance monitoring of criteria pollutants

Representative path-integrated data

Easily calibrated

Operates with a minimum of maintenance

Approved by MCERTS, TÜV and U.S. EPA

OPSIS AB

Box 244
SE-244 02 Furulund, Sweden
Telephone Int +46 46 72 25 00
Telefax Int +46 46 72 25 01
E-mail info@opsis.se
URL <http://www.opsis.se>